



Baseboard heater ● S5

Applications

Only this heater guarantees the real Soft Heat comfort of the innovative and attractive line. It also assures a consistent blanket of warm air throughout the room from the beginning to the end of the heating season.

Colours : White or Almond.
Construction: 20 gauge
Protection against overheating.
Rounded edges at the corners.
Power: 300 to 2500 Watts.
Tension: 120, 208, 240, 347 and 600 volts.

Element : Stainless steel centre fixed tube with floating edges in a nylon sleeve to eliminate the noise of the expanding and contracting metal throughout the heating cycles.

Warranty - 10 years warranty on the electric heating element applies to the initial end user;
1 year on the other components.

Control

The built in thermostat can be installed from either end.



Watts	120v	208v	240v	347v	600v	Length
300	S5W-03	S5W-03	S5W-03			21.2/540
500	S5W-05	S5W-05	S5W-05	S5W-05		28/710
750	S5W-07	S5W-07	S5W-07	S5W-07	S5W-07	36.2/920
1000	S5W-10	S5W-10	S5W-10	S5W-10	S5W-10	44.5/1130
1250	S5W-12	S5W-12	S5W-12	S5W-12	S5W-12	52.8/1340
1500	S5W-15	S5W-15	S5W-15	S5W-15	S5W-15	61/1550
1750		S5W-17	S5W-17	S5W-17	S5W-17	69.3/1760
2000		S5W-20	S5W-20	S5W-20	S5W-20	77.6/1970
2250		S5W-22	S5W-22	S5W-22	S5W-22	85.8/2180
2500		S5W-25	S5W-25	S5W-25	S5W-25	94.1/2390

Remove the "W" from the part number for the almond units.
The units design for 240v can function at 208v, the result will be 75% of the original power (ex: 300w=225w).

For ordering, add the voltage to the part number.
Ex: for 500w/240v white the number would be: S5W-05-240.

*Low density units are available upon demand.

Baseboard Heater Accessories

S5

Temperature regulation

Almond	White	Description	Voltage	Amp.
S5-TSB	S5W-TSB	Unipolar	120, 208, 240	17
S5-TSB-T	S5W-TSB-T	Unip., anti-vandalism	120, 208, 240	17
S5-TDB	S5W-TDB	Bipolar	120, 208, 240	17
S5-TDB-T	S5W-TDB-T	Bipolar anti-vandalism	120, 208, 240	17
S5-TSB-6	S5W-TSB-6	Unipolar	347, 600	10
S5-TSB-6T	S5W-TSB-6T	Unip., anti-vandale	347, 600	10
S5-TDB-6	S5W-TDB-6	Bipolar	347, 600	10
S5-TDB-6T	S5W-TDB-6T	Bipolar anti-vandalism	347, 600	10

1) Range of adjustment : 5 at 37 °C (40 à 100 °F).

2) Off" Position.

4) Factory or on-site installation (For factory installation add the thermostat number to the part number).

Electronic Relay

Catalog no	Voltage	Amp.
S5-RTK120	120	25
S5-RTK208	208	25
S5-RTK240	240	25
S5-RTK347	347	17
S5-RTK600	600	10
S5-RK	120, 208, 240, 347, 600v	25, 17, 10

