

# **PPG Series**

# **Features**

## Color

- Standard: white.
- Optional (upcharge applicable): almond, metallic silver, bronze, metallic charcoal, aluminum, semi-gloss black, sand.

# Finish

- Standard: epoxy/polyester powder paint.

### Voltage

- 240/208V, 1-phase.

## Construction

- So sturdy, it can be used as a step (18-gauge steel).
- Linear high-limit temperature control with automatic reset. 1

# **Heating element**

- Stainless steel tubular heating element with aluminum fins. 2
- Floating heating element on high-temperature nylon bushings reducing expansion noises. 3

# **Watt density**

- Average standard watt density of 209W/ft.

# Control

- Wall thermostat (not included).

Global Commander highly recommends using an electronic wall thermostat for greater comfort.

### Installation

- Mounting holes spaced on 2 in. (51 mm) intervals for an easy installation.

### Warranty

- 1-year against defects.
- 10-year on the heating element.

# **Application**

- Patio door, bay window, commercial building, office building, condos, restaurant.

# **Models**

								Packaging Dimensions						
Product #	Watts 240/208V	Product Length		Net Weight		Gross Weight		A		В		c		
		in.	mm	lb	kg	lb	kg	in.	mm	in.	mm	in.	mm	
PPG1000BL	1000/750	60	1525	20	9.1	20.5	9.3	61	1549.4	4 5/16	109.5	4 5/16	109.5	
PPG1250BL	1250/938	72	1830	24.5	11.1	25	11.4	72 13/16	1849.4	4 5/16	109.5	4 5/16	109.5	

Standard color is white.

Upcharge available for optional colors shown in the color chart section.

