



# 120V Preassembled Heating Cable for Pipe Freeze Protection

## RFG-P Series

### Features

#### Nominal voltage

- 120V.

#### Linear density

- 7 Watts per foot.

#### Cold lead length

- 30 in. (0.76 m).

#### Outer jacket

- PVC.

#### Bus wire

- Nickel plated copper.

#### Minimum bend radius

- 5/16 in. (8 mm).

#### Included hardware

- Built-in bi-metal thermostat energizes the cable when temperature falls below 4 °C (40 °F).
- Grounded 3-pronged plug with indicator light to show when the cable is on.

### Installation

- Never cut or shorten the heating cable.
- Not for residential use in the United States.
- Installation under the insulation of the pipe.
- For indoor and outdoor applications.
- Minimum installation temperature: 0 °C (32 °F).

### Warranty

- 1-year on the heating cable.

### Application

- Metallic and non-metallic pipes.
- Helps to prevent damage caused by frozen pipes.

## Models

Product # <sup>1</sup>	Watts	Product Length		Gross Weight		Packaging Dimensions					
		ft.	m	lb	kg	A		B		C	
						in.	mm	in.	mm	in.	mm
RFG-P003	21	3	0.9	0.8	0.4	7	178	9	229	2	51
RFG-P006	42	6	1.8	1	0.5	7	178	9	229	2	51
RFG-P009	63	9	2.7	1.4	0.6	7	178	9	229	2	51
RFG-P012	84	12	3.7	1.7	0.8	7	178	10	254	2	51
RFG-P015	105	15	4.6	2.3	1.1	7	178	10	254	2	51
RFG-P018	126	18	5.5	2.7	1.2	9	229	9	229	3	76
RFG-P024	168	24	7.3	2.9	1.3	9	229	9	229	3	76
RFG-P030	210	30	9.0	3	1.4	9	229	9	229	3	76
RFG-P040	280	40	12.2	3.5	1.6	9	229	9	229	3	76
RFG-P060	420	60	18.3	3.9	1.8	9	229	9	229	3	76
RFG-P080	560	80	24.4	5	2.3	10	254	10	254	4	102

<sup>1</sup> Must be plugged into a 120V outlet fitted with ground fault protection device (GFCI).

