

## **VCG Series**

### **Features**

#### Color

- Standard: white.

#### Finish

- Standard: epoxy/polyester powder paint.

#### Voltage

- 120V, 240/208V, 1-phase.

#### Construction

- Shock-resistant cast aluminum front cover.
- 20-gauge steel.
- High-limit temperature control with automatic reset.

#### Fan

- Whisper-quiet squirrel-cage fan.
- Factory-lubricated, two-speed motor.

## **Heating element**

- Nickel-chromium alloy stitched wire protected by mica insulators.
- Heating element provides instant heat.

### Contro

- Operating modes adapted for all requirements (comfort, economy, frost-free, full power, standby mode).
- Built-in electronic digital thermostat/timer with backlit display that can be used as a night light.

- Electronic thermostat with 2 triacs automatically switches from 750W to 1500W when needed.
- Keypad lock function that eliminates unwanted temperature adjustments and the use of the thermostat modes.

#### Installation

- 6 in. (152 mm) minimum clearance to floor.
- May be recessed or surface-mounted without adaptor in 2 in. X 3 in. stud partitions with gypsum.
- Easy installation and connection with mounting screws and knockouts (mounting screws included).
- Template included.
- Also available with connection to a grounded 3-pronged plug on a dedicated circuit (VCG1502BL-CORD-TH), surface-mounted only. 1

## Warranty

- 5-year against defects.

## Application

- Hallways, bathrooms, shower rooms, dining rooms, kitchens, corridors.

# **Models**

									Packaging Dimensions				
Product #	Volts	Watts		Net Weight		Gross Weight		Α		В		С	
		min.	max.	lb	kg	lb	kg	in.	mm	in.	mm	in.	mm
VCG1500BL-TH	240/208	750/563	1500/1125	12.8	5.8	12.8	5.8	12.5	318	17	432	4.5	114
VCG1502BL-CORD-TH	120	750	1500	17	7.7	17	7.7	12.5	318	17	432	4.5	114

Standard color is white.



