



# Traditional Style Baseboard Heater

## PEG Series

### Features

#### Color

- Standard: white, almond.
- Optional (upcharge applicable): metallic silver, bronze, metallic charcoal, aluminum, semi-gloss black, sand.
- Custom colors available upon request.

#### Finish

- Standard: 4H pencil hardness epoxy/polyester powder coat paint.
- May be repainted with any interior paint.

#### Voltage

- 120V, 240/208V, 1-phase.

#### Construction

- Robust 22-gauge steel body.
- Sturdy 20-gauge steel front panel.
- Welded 20-gauge steel connection box.
- Rounded corners.
- Linear high-limit temperature control with automatic reset.

#### Heating element

- Stainless steel tubular heating element with aluminum fins.
- Floating heating element on high-temperature nylon bushings reducing expansion noises.

#### Control

- Built-in thermostat kit can be installed at either end.

*Global Commander highly recommends using an electronic wall thermostat for greater comfort and efficiency.*

#### Installation

- Installation directly on the floor.
- No need to disassemble for electrical connection or wall attachment.
- Built-in single-screw wire holder on the back for quick connection box access from either end.
- Two rows of oval mounting holes with centering mark for ease of installation.
- Raceway and side knock-outs for baseboard interconnection.

#### Warranty

- 5-year warranty against defects.
- Lifetime on the heating element.

#### Application

- Kitchen, living room, family room, bedroom, bay window, commercial building, office building, condo, restaurant.

## Models

Product #	Watts 120V	Product #	Watts 240/208V	Product Length <sup>1</sup>		Net Weight		Gross Weight		Packaging Dimensions					
				in.	mm	lb	kg	lb	kg	A		B		C	
PEGU0352	350	PEGU0350	350/263	24	610	4.7	2.1	4.9	2.2	24 1/2	622	2 3/4	70	6 1/4	159
PEGU0502	500	PEGU0500	500/375	27 3/4	702	5.7	2.6	5.9	2.7	28 1/4	717	2 3/4	70	6 1/4	159
PEGU0702	700	PEGU0700	700/525	36	915	6.7	3.0	6.9	3.1	36 1/2	927	2 3/4	70	6 1/4	159
PEGU0752	750	PEGU0750	750/563	37 3/4	956	7.0	3.2	7.2	3.3	38 1/4	972	2 3/4	70	6 1/4	159
PEGU1002	1000	PEGU1000	1000/750	48	1217	8.7	3.9	9	4.1	48 1/2	1232	2 3/4	70	6 1/4	159
PEGU1252	1250	PEGU1250	1250/938	60	1524	10.7	4.9	11	5	60 1/2	1537	2 3/4	70	6 1/4	159
PEGU1502	1500	PEGU1500	1500/1125	72	1829	12.7	5.7	13	5.9	72 1/2	1842	2 3/4	70	6 1/4	159
-	-	PEGU1850	1850/1390	84	2134	14.6	6.6	15	6.8	84 1/2	2146	2 3/4	70	6 1/4	159
-	-	PEGU2000	2000/1500	96	2439	16.6	7.5	17	7.7	96 1/2	2451	2 3/4	70	6 1/4	159
-	-	PEGU2250 <sup>2</sup>	2250/1688	93	2364	16.2	7.3	16.6	7.5	93 1/2	2375	2 3/4	70	6 1/4	159
-	-	PEGU2500 <sup>2</sup>	2500/1875	102 1/4	2596	17.8	8.0	18.2	8.3	102 3/4	2610	2 3/4	70	6 1/4	159

## Options

Product # Kit	Description
KIT-PEG-T1	Single-pole bi-metal thermostat: 25A at 120-277V - 10A at 347-600V, with a control knob
KIT-PEG-T2 <sup>3</sup>	Double-pole bi-metal thermostat: 25A at 120-277V - 10A at 347-600V, with a control knob

<sup>1</sup> Nominal length  $\pm 1/8"$  (3 mm).

<sup>2</sup> These models must be ordered in pairs to reduce shipping damages.

<sup>3</sup> "Off" position.

Add "BL" for white, "AM" for almond.

Upcharge available for optional colors shown in the color chart section.

