



Requires a grounded  
3-pronged outlet



NEMA 6-30R  
30A, 250VAC



## Portable Heater

### CCG Series

#### Features

##### Color

- Standard: almond.

##### Finish

- Standard: epoxy/polyester powder paint.

##### Voltage

- 240/208V, 1-phase.

##### Construction

- Handle may be used as a reel for the electrical cable.
- 6 ft. (2 m) molded electrical cable for extra durability.
- Safely recessed thermostat knob reduces heater size to a minimum.
- High-limit temperature control with automatic reset (first level) and single operation thermal fuse (second level).

##### Fan

- Totally enclosed motor permanently lubricated (-MF model).
- Open motor permanently lubricated (-MO model).

*Note: The open motor is not intended for use in a dusty environment.*

- 300 cfm fan.

##### Heating element

- Helical coil nickel-chromium alloy wire protected by ceramic insulators.
- Heating element provides instant heat.

##### Temperature rise

- 28 °C (51 °F).

##### Control

- Built-in thermostat included.

##### Installation

- Must be plugged into a grounded 3-pronged outlet, 30A, 250VAC (not supplied).

*Note: Always unplug heater when not in use.*

##### Warranty

- 1-year warranty against defects.

##### Application

- Construction area, workshop, garage.

### Models

Product # <sup>1</sup>	Watts 240/208V	Motor type	Net Weight		Gross Weight		Packaging Dimensions							
							A		B		C			
			lb	kg	lb	kg	in.	mm	in.	mm	in.	mm		
CCGU4800AM-MF-TB6	4800/3600	Enclosed	16	7.2	16.75	7.3	12 1/2	318	10 1/2	267	14 1/4	362		
CCGU4800AM-MO-TB6	4800/3600	Open	16	7.2	16.75	7.3	12 1/2	318	10 1/2	267	14 1/4	362		

Standard color is almond.

