



Requires a grounded
3-pronged outlet



NEMA 6-30R
30A, 250VAC



Portable Heater

CCG Series

Features

Color

- Standard: almond.

Finish

- Standard: epoxy/polyester powder paint.

Voltage

- 240/208V, 1-phase.

Construction

- Handle may be used as a reel for the electric cable.
- 6 ft. (2 m) molded electric cable for extra durability.
- Safely recessed thermostat knob reduces heater size to a minimum.
- High-limit temperature control with automatic reset.

Fan

- Totally enclosed motor (-MF model).
- Open motor (-MO model).

Note: The open motor is not intended for use in a dusty environment.

- 300 cfm fan.

Heating element

- Helical coil nickel-chromium alloy wire protected by ceramic insulators.
- Heating element provides instant heat.

Temperature rise

- 28 °C (82 °F).

Control

- Built-in thermostat included.

Installation

- Must be plugged into a grounded 3-pronged outlet, 30A, 250VAC (not supplied).

Note: Always unplug heater when not in use.

Warranty

- 1-year against defects.

Application

- Construction area, workshop, garage.

Models

| Product # ¹ | Watts 240/208V | Motor Type | Net Weight | | Gross Weight | | Packaging Dimensions | | | | | | |
|------------------------|-------------------|------------|------------|-----|--------------|-----|----------------------|-----|--------|-----|--------|-----|----|
| | | | lb | kg | lb | kg | A | | B | | C | | |
| | | | | | | | | in. | mm | in. | mm | in. | mm |
| CCG4800AM-MF-TB6 | 4800/3600 | Enclosed | 16 | 7.2 | 16.75 | 7.3 | 12 1/2 | 318 | 10 1/2 | 267 | 14 1/4 | 362 | |
| CCG4800AM-MO-TB6 | 4800/3600 | Open | 16 | 7.2 | 16.75 | 7.3 | 12 1/2 | 318 | 10 1/2 | 267 | 14 1/4 | 362 | |

¹Built-in thermostat included.
Standard color is almond.

